

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-3. (Canceled)

4. (Previously Presented) An apparatus for interfacing video information in a computer system, comprising:

a main body, which outputs a video signal, a horizontal sync signal, a vertical sync signal, and video signal display type information identifying a video type of the video signal, the video signal display type information including a display code that designates the video signal display type, wherein the video signal display type information is divided to comprise divided display type information having at least two parts, and wherein the divided display type information is embedded into the horizontal sync signal and at least one of R, G, and B video signals forming the video signal, respectively; and

a monitor, which detects the type of display for the corresponding video signal in accordance with the display type information, and displays the outputted video signal in accordance with the detected display type.

5. (Previously Presented) A video interface, comprising:

a main body, which provides information relative to a display type of a video signal, the information being divided to comprise divided display type information having at least two parts, wherein a first part of the divided display type information is embedded into a horizontal sync signal, and wherein a second part of the divided display type information is embedded into at least one of R, G, and B video signals comprising the video signal, respectively, and outputs the video signal, the horizontal sync signal, and a vertical sync signal; and

a monitor which detects the display type of the corresponding video signal in accordance with the display type information outputted from the main body, and displays the video signal in accordance with the detected display type, wherein the information relative to the display type comprises a display code that designates the video signal display type.

Claims 6-7. (Cancelled)

8. (Previously Presented) A method of interfacing video information, comprising:

transmitting video signal display type information, horizontal and vertical sync signals, and a video signal from a main body to a monitor, the video signal display type

information being divided to comprise divided display type information having at least two parts, and wherein a first part of the divided display type information is embedded into the horizontal sync signal, and wherein a second part of the divided display type information is embedded into at least one of R, G, and B video signals comprising the video signal, respectively, the video information display type information including a display code that designates a video display type; and

detecting a display type of the video signal transmitted from the main body using the video signal display type information, and displaying the video signal to match the display type.

9. (Previously Presented) The method as claimed in claim 8, wherein the display type information comprises a recognition code for designating a kind of the corresponding display type information, and data corresponding to the recognition code.

10. (Original) The method as claimed in claim 9, wherein the recognition code is composed of two bits.

11. (Original) The method as claimed in claim 9, wherein the data includes a number of dots in a horizontal period, a number of backporches in the horizontal period, a

number of horizontal lines in a vertical period, and a number of horizontal lines of a backporch in the vertical period.

Claims 12-13. (Canceled)

14. (Previously Presented) A method of interfacing video information, comprising:

dividing display type information of a video signal into at least two parts;

transmitting divided display type information of the video signal in each of a horizontal sync signal and the video signal, respectively, from a main body, the display type information including a display code that designates the video signal display type; and

detecting a display type of the transmitted video signal using the display type information.

15. (Original) The method as claimed in claim 14, wherein the main body synchronizes the display type information with the vertical sync signal.

16. (Previously Presented) The method as claimed in claim 14, further comprising transmitting a vertical sync signal from the main body to the monitor, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

17. (Previously Presented) A method of interfacing video information, comprising:

dividing display type information of R, G, B video signals, the display type information including a recognition code that designates the video signal display type and data corresponding to the recognition code;

embedding the divided display type information into a horizontal sync signal and at least one of the R, G, and B video signals, respectively;

transmitting to a monitor the horizontal sync signal, a vertical sync signal, and the video signals;

decoding and reassembling the display type information; and

detecting a display type of the transmitted video signal using the reassembled display type information.

18. (Original) The method as claimed in claim 17, wherein the main body synchronizes the display type information with the vertical sync signal.

19. (Original) The method as claimed in claim 17, wherein a clock pulse for recognizing the display type information is included in the vertical sync signal.

Claims 20-26. (Cancelled)

27. (Previously Presented) A method of interfacing video information, comprising:

dividing display type information of a video signal, the display type information including a display code that designates a video signal display type;

embedding the divided display type information into at least one of a horizontal sync signal, an R video signal, a G video signal, and a B video signal;

embedding a clock pulse for recognizing the display type information in a vertical sync signal;

transmitting the horizontal sync signal, the R video signal, the G video signal, the B video signal, and the vertical sync signal from a main body to a monitor; and

detecting the video signal display type using the display type information.

28. (Previously Presented) The method of claim 27, wherein the display code comprises a recognition code that designates the video display type and data corresponding to the recognition code.

Claims 29-32. (Cancelled)

33. (Previously Presented) The apparatus of claim 4, wherein the display code comprises a recognition code that designates the video display type and data corresponding to the recognition code.

34. (Previously Presented) The apparatus of claim 4, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

35. (Previously Presented) The interface of claim 5, wherein the display code comprises a recognition code that designates the signal display type and data corresponding to the recognition code.

36. (Previously Presented) The interface of claim 5, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

37. (Previously Presented) The method of claim 8, wherein the display code comprises a recognition code that designates the video display type and data corresponding to the recognition code.

38. (Previously Presented) The method of claim 8, wherein the vertical sync signal comprises a clock pulse for recognizing the display type information.

Claims 39-40. (Cancelled)

41. (Previously Presented) The method of claim 14, wherein the display code comprises a recognition code that designates the video signal display type and data corresponding to the recognition code.

Claims 42-43. (Cancelled)

44. (Currently Amended) ~~The apparatus as claimed in claim 1;~~ An apparatus for interfacing video information, comprising:

a main body, which outputs a video signal and corresponding display type information, the display type information including a data-identifying recognition code that identifies a specific kind of the corresponding display type information, and data corresponding to the data-identifying recognition code; and

a monitor, which detects a display type of the corresponding video signal in accordance with the display type information, and displays the video signal outputted from the main body in accordance with the detected display type, wherein the display type information is divided to comprise at least two parts, and wherein the divided display type information is embedded into a horizontal sync signal and at least one of the R, G, and B video signals, respectively.

45. (Currently Amended) ~~The interface as claimed in claim 2;~~ A video interface, comprising:

a main body, which outputs a video signal through a video signal line, and outputs information relating to the video signal display type, the information relating to the video signal display type including a display code that designates the video signal display type, wherein the display code comprises a data-identifying recognition code that identifies a specific kind of the corresponding video signal display type information, and the information corresponding to the data-identifying recognition code; and

a monitor, which detects the display type of the corresponding video signal in accordance with the display information, and displays the video signal outputted from the main body in accordance with the detected display type, wherein the information relating to the video signal display type is divided to comprise divided display type information having at least two parts, and wherein the divided display type information is embedded into a horizontal sync signal and at least one of the R, G, and B video signals, respectively.

46. (Currently Amended) ~~The method as claimed in claim 12;~~ A method of interfacing video information, comprising:

transmitting display type information of a video signal in communication data, along with horizontal and vertical sync signals from a main body to a monitor, the display

type information comprising a display code that designates a video signal display type, wherein the display code comprises a data-identifying recognition code that identifies a specific kind of the corresponding display type information, and data corresponding to the data-identifying recognition code; and

detecting a display type of the transmitted video signal using the display type information, and displaying the video signal to match the display type, wherein the display type information is divided to comprise divided display type information having at least two parts, and wherein at least one part of the divided display type information is embedded into one of a horizontal sync signal and at least one of the R, G, and B video signals, respectively.

47. (Canceled)

48. (Currently Amended) ~~The apparatus as claimed in claim 26;~~ An apparatus for interfacing video information in a computer system, comprising:

a main body, which outputs a video signal, a horizontal sync signal, a vertical sync signal, and video signal display type information identifying a video type of the video signal, the video signal display type information including a display code that designates the video signal display type, wherein the video signal display type information is divided to comprise divided display type information having at least two parts, and wherein the divided

display type information is embedded into the horizontal sync signal and at least one of R, G, and B video signals forming the video signal, respectively; and

a monitor, which detects the type of display for the corresponding video signal in accordance with the display type information, and displays the outputted video signal in accordance with the detected display type, wherein the display type information is divided to comprise divided display type information having at least two parts, and wherein the divided display type information is embedded into a horizontal sync signal and at least one of the R, G, and B video signals, respectively.

Claims 49-54. (Canceled)